NEO TOUCH

COMPACT TOUCH ELECTRONIC DEADBOLT









- ANSI/BHMA Grade 3 Security
- Easy installation with a screw driver
- Back-up key override
- Vacation mode
- Low battery indicator



FAULTLESS





UNCOMPROMISED SECURITY

- ANSI Grade 3 Security
- ANSI A156.25 compliant-resistant to dust, rain, and corrosion under variable temperatures
- Keypad is temporarily disabled after 4 consecutive incorrect entries

SPECIAL FUNCTIONS

- Vacation mode deactivates all user codes temporarily
- Single-entry Code for one-time usage only
- Automatic relocking mode
- Resistive touch, works with gloves and wet hands

EASY INSTALLATION

- Replaces your existing deadbolt
- Easy installation with a Philips screwdriver
- Fits most standard door preparations



PRODUCT SPECIFICATION

Programming code: 1 set (6 digits)

User code capacity: 10 sets (4-6 digits)

Finish: Satin Nickel / Aged Bronze / Matte Black

Door bore hole: 2-1/8"(54 mm) or 1-1/2"(38 mm)

Door thickness: 1-3/8"(35 mm) to 2"(51 mm)

Backset: 2-3/8"(60 mm) and 2-3/4"(70 mm)

Back-light color: White

Power: Four AA 1.5V alkaline batteries

Operating temperature : -31°F to 150.8°F(-35°C to 66°C)

(Temperature tolerance could vary due to different weather conditions)