

TOUCH-BOLT™

THE SMART TOUCH EXPERIENCE
Z-WAVE PLUS SERIES



- Easy installation with a Philips screwdriver
- Vacation mode (deactivates all user codes temporarily)
- Connect and operate from anywhere
- Auto-lock with adjustable delay



FAULTLESS

FAULTLESS

Electronic Touchscreen Deadbolt



Great Convenience

- Touch to activate, touch to lock
- Connect your Z-Wave smart home system and operate from anywhere
- Holds up to 25 user codes
- Holds up to 4 single-entry codes
- Vacation mode (deactivates all user codes temporarily)
- Auto-lock with adjustable delay
- Back-up mechanical keyway

Uncompromised Security

- ANSI A156.25 compliant - resistant to dust, rain, and corrosion under variable temperatures
- 4-digit random guiding code prevents code-probing
- Touch screen / Keypad is temporarily disabled after 4 consecutive incorrect entries

Easy Installation

- Easy installation with a Philips screwdriver
- Fits most standard door preparations

Product Specification



Style 1 Style 2

User codes : 25 sets (4 to 8 digits each)



Style 1

25 sets (4 to 8 digits each)



Style 1 Style 2 Style 3 Style 4

25 sets (4 to 6 digits each)

Programming code :	1 set	1 set	1 set
Key :	2	2	2
Size (WxHxD) :	Exterior lock body : 138 mm (Style *2_142 mm) x 65 mm x 28 mm Interior lock body : 174 mm x 70 mm x 38 mm	Exterior lock body : 160 mm x 80 mm x 73mm Interior lock body : 174 mm x 70 mm x 38 mm	Exterior lock body : 99 mm (Style *1_124 mm) x 68 mm (Style *1_84 mm) x 22 mm (Style *1_35 mm) Interior lock body : 174 mm x 70 mm x 38 mm
Model :	Style1 / Style2	Style1	Style1 / Style2 / Style3 / Style4
Finish :	Satin Nickel / Aged Bronze / Bright Chrome	Satin Nickel / Aged Bronze	Satin Nickel / Aged Bronze
Door bore hole :	2-1/8"(54 mm) or 1-1/2"(38 mm)	2-1/8"(54 mm) or 1-1/2"(38 mm)	2-1/8"(54 mm) or 1-1/2"(38 mm)
Door thickness :	1-3/8"(35 mm) to 2"(51 mm)	1-3/8"(35 mm) to 2"(51 mm)	1-3/8"(35 mm) to 2"(51 mm)
Adjustable backset :	2-3/8"(60 mm) and 2-3/4"(70 mm)	2-3/8"(60 mm) and 2-3/4"(70 mm)	2-3/8"(60 mm) and 2-3/4"(70 mm)
Power :	DC 6V (Four AA 1.5V alkaline batteries)	DC 6V (Four AA 1.5V alkaline batteries)	DC 6V (Four AA 1.5V alkaline batteries)
Operation temperature :	-31 F° to 150.8 F° (-35 C° to 66 C°) (Temperature tolerance could vary due to different weather conditions)		
ANSI Grade :	2	2	3