

TOUCH-BOLT™

THE SMART TOUCH EXPERIENCE

TOUCH-BOLT SERIES ELECTRONIC DEADBOLT



- Touch to activate, touch to lock
- Replaces your existing deadbolt
- Easy installation with a Philips screwdriver
- ANSI Grade 2 quality – Deadbolt operates over 150,000 times
- Vacation mode (deactivates all user codes temporarily)
- Auto-lock with adjustable delay (10 - 99 seconds)



FAULTLESS

FAULTLESS

Electronic Touchscreen Deadbolt



Great Convenience

- Touch to activate, touch to lock
- Holds up to 25 user codes
- Holds up to 4 single-entry codes
- Volume control (adjustable to work with environments)
- Vacation mode (deactivates all user codes temporarily)
- Auto-lock with adjustable delay (10 - 99 seconds)
- Back-up mechanical keyway

Uncompromised Security

- ANSI Grade 2 quality – deadbolt operates over 150,000 times
- ANSI A156.25 compliant - resistant to dust, rain, and corrosion under variable temperatures
- 4-digit random guiding code prevents code-probing
- Touch screen is temporarily disabled after 4 consecutive incorrect entries

Easy Installation

- Replaces your existing deadbolt
- Easy installation with a Phillips screwdriver
- Fits most standard door preparations
- Only requires four AA alkaline batteries to operate
- Online video instruction available

Product Specification

User codes : 25 sets (4 to 8 digits each)

Programming code : 1 set

Key : 2

Size (WxHxD) : Exterior lock body : 66 mm x 139 mm x 28 mm
Interior lock body : 70 mm x 174 mm x 38 mm

Finish : Satin Nickel / Aged Bronze / Matte Black

Door bore hole : 2-1/8"(54 mm) or 1-1/2"(38 mm)

Door thickness : 1-3/8"(35 mm) to 2"(51 mm)

Adjustable backset : 2-3/8"(60 mm) and 2-3/4"(70 mm)

Touch Screen Back-light color : White

Power : DC 6V (Four AA 1.5V alkaline batteries)

Operation temperature : -31 F° to 150.8 F° (-35 C° to 66 C°)
(Temperature tolerance could vary due to different weather conditions)

